

Welding Curtain With Hooks

Item No.: 361362522

Product information

All hazardous radiation is filtered by the welding curtain, according to the standard EN ISO 25980:2014·Health and safety in welding and allied processes – Transparent welding curtains, strips and screens for arc welding processes. The welding curtain must be used to prevent injury to other personnel from welding operations. It also reduces light emission, but it is still possible to view through it. The curtain is made of self-extinguishing material.

- Hooks are supplied with the welding curtain.



Features

- Curtain comes complete with 7 holes and 7 heavy-duty hooks
- Maximum pipe diameter which the hooks will fit on is 41 mm. In order for the curtain to be drawn freely the pipe should be less than 30 mm
- Curtain size is 2.0 m high and 1.3 m wide

Benefits

- Clear view during welding which is a safety requirement i.e., immediately visible and alert personnel if something is wrong behind the curtain vs. other non-standard materials used e.g. tarpaulin which totally block clear view
- With the hooks, the curtain can be put in a frame or hooked up on an existing pipe or wire. It is also possible to join two or more curtains together by the use of snap on buttons along the side
- Block harmful effects of the UV rays generated during welding
- Compliance with EN ISO 25980:2014 and OCIMF SIRE requirements

Specification

General:

Invent Hazard Material (IMO/EU) classification	NA
--	----